

TABLE OF CONTENTS

SECTION 1	INTRODUCTION	59
1.1	A BRIEF DESCRIPTION OF THE PROPOSED ACTIVITY	59
1.2	PPC DE HOEK	61
1.3	PPC DE HOEK CEMENT MANUFACTURING PLANT	61
1.4	THE LEGAL FRAMEWORK	64
1.4.1	<i>Other Legislation Considered</i>	64
1.4.2	<i>Plan of Study for Scoping</i>	73
1.4.3	<i>Provisions of the approval of the Plan of Study for Scoping</i>	75
1.4.4	<i>Plan of Study for Environmental Impact Assessment</i>	75
1.4.5	<i>Approval of the Scoping Report and Plan of Study for Environmental Impact Assessment</i>	77
1.4.6	<i>Process background and programme</i>	79
1.5	ENVIRONMENTAL IMPACT ASSESSMENT REPORT	79
1.5.1	<i>Methodology</i>	79
1.5.2	<i>General Terms of Reference</i>	80
1.5.3	<i>The Environmental Consultant</i>	80
1.6	THE PROPONENT	80
1.6.1	<i>History of PPC</i>	80
1.7	PROPONENT'S MOTIVATION AND OVERALL COMMITMENT FOR THE USE OF SECONDARY MATERIALS	81
1.8	THE PRECAUTIONARY APPROACH	84
SECTION 2	THE CEMENT MANUFACTURING PROCESS	85
2.1	A DETAILED DESCRIPTION OF THE CEMENT MAKING PROCESS AT DE HOEK	85
2.1.1	<i>Primary Raw Materials</i>	85
2.1.2	<i>Secondary Raw Materials</i>	87
2.1.3	<i>Clinker burning</i>	87
2.1.4	<i>Clinker</i>	90
2.1.5	<i>Milling and Final Product (Cement)</i>	90
2.1.6	<i>Cement dispatch</i>	90
2.1.7	<i>Summary of inputs and outputs</i>	91
SECTION 3	ENVIRONMENTAL ASPECTS OF SECONDARY MATERIALS CO-PROCESSING IN THE MAKING OF CEMENT	92
3.1	INTRODUCTION TO SECONDARY MATERIALS CO-PROCESSING	92
3.1.1	<i>Why is the Cement Kiln Suitable for Co-Processing of Secondary Materials?</i>	92
3.1.2	<i>International use of Secondary Materials</i>	93
3.1.3	<i>International Trends</i>	95
3.1.4	<i>Specified limits on Secondary Material Inputs</i>	98
3.1.5	<i>Use of Secondary Materials at PPC</i>	99
3.2	EMISSIONS TO ATMOSPHERE	100
3.2.1	<i>Inherent Combustion Gas Cleaning Capability</i>	101
3.2.2	<i>Nitrogen oxides (NO_x) formation</i>	101
3.2.3	<i>Carbon Monoxide (CO) formation</i>	103
3.2.4	<i>Volatile Components</i>	104
3.2.5	<i>Organic Compounds</i>	105
3.2.6	<i>Sulphur Compounds</i>	105
3.2.7	<i>Behaviour of Volatile Components</i>	106
3.2.8	<i>Evaporation and condensation in the kiln system (circulation)</i>	107
3.2.9	<i>Affinity between the Volatile Components</i>	108
3.2.10	<i>Potential for Evaporation</i>	108
3.2.11	<i>Molecular Ratio of Sulphur and Alkalis</i>	108
3.2.12	<i>Sulphur Dioxide (SO₂) entrapment in the preheater system</i>	109
3.2.13	<i>Ammonia (NH₃)</i>	109
3.2.14	<i>Halogens (Cl and F)</i>	110
3.2.15	<i>Metals</i>	110

	3.2.16	Dioxins and Furans	111
	3.2.17	Dust	115
3.3		CONSERVATION OF NATURAL RESOURCES	116
3.4		LIQUID EFFLUENT	117
3.5		POTENTIAL FOR SURFACE WATER, SOIL AND GROUNDWATER CONTAMINATION DURING TRANSPORTATION OF HAZARDOUS WASTES	117
3.6		POTENTIAL FOR SURFACE WATER, SOIL AND GROUNDWATER CONTAMINATION ON-SITE	118
3.7		GENERATION OF SOLID WASTE	118
3.8		GREENHOUSE GAS REDUCTION	119
3.9		REDUCTION OF WASTE SENT TO LANDFILL	119
3.10		POTENTIAL IMPACT ON WATER QUALITY DUE TO USE OF CEMENT MADE FROM SECONDARY MATERIALS INCLUDING PRODUCT LEACHING	120
3.11		PROCESS CONTROL AND KILN STABILITY	123
3.12		SELF-REGULATION AND QUALITY ASSURANCE	126
3.13		LEGISLATION APPLICABLE TO THE USE OF SECONDARY MATERIALS	126
	3.13.1	Occupational Health and Safety Act (Act 85 of 1993)	127
	3.13.2	Environment Conservation Act, 1989 (Act 73 of 1989), National Water Act, 1998 (Act 36 of 1998) and the Water Services Act, 1997 (Act 108 of 1997)	130
	3.13.3	Minimum Requirements for the Handling, Classification and Disposal of Hazardous Waste (DWAF, 2nd edition, 1998)	130
	3.13.4	National Policy Development Process for High Temperature Thermal Waste Treatment and Co-processing of AFRs in Cement Kilns (Proposed)	132
	3.13.5	CAPCO Limits and Design Criteria	136
3.14		INTERNATIONAL EMISSIONS LIMITS	139
SECTION 4		PPC'S SECONDARY MATERIALS CO-PROCESSING PROGRAMME	141
4.1		SAMPLING AND ACCEPTANCE OF SECONDARY MATERIALS PRIOR TO PROCESSING	141
	4.1.1	Introduction	141
	4.1.2	Initial Screening	142
	4.1.3	Waste Identification Analysis	143
	4.1.4	Sampling Protocols	143
	4.1.5	Suitability for the Cement Kiln (Desktop Study)	144
	4.1.6	Plant Trial	145
	4.1.7	Implementation	145
	4.1.8	Regular Cross Check	147
	4.1.9	External verification, auditing and reporting	148
4.2		PHYSICAL OPERATION OF SECONDARY MATERIALS PROCESSING	150
	4.2.1	Collection from Generator and Transport to site	150
	4.2.2	On-site storage	152
	4.2.3	Feed to the kiln	154
4.3		SELECTION OF INJECTION POINT	157
4.4		PROCESS MONITORING DURING OPERATION	157
4.5		EMISSIONS CONTROL AT PPC'S OPERATIONS	158
4.6		EMISSIONS MONITORING DURING OPERATION	158
4.7		AUDITING AND REPORTING DURING OPERATION	159
4.8		EMERGENCY PREPAREDNESS AND RESPONSE	160
4.9		HEALTH AND SAFETY	160
4.10		EMPLOYEE TRAINING	161
4.11		TRIAL BURN	161
	4.11.1	Schedule of trial burns	161
	4.11.2	Waste to be sourced	162
	4.11.3	Blending of Wastes for Trial Burn	162
	4.11.4	Storage and Feed to Kiln	163
	4.11.5	Process Monitoring	164
	4.11.6	Independent audit	165
	4.11.7	Emissions Monitoring and Reporting	165
SECTION 5		ASSUMPTIONS, LIMITATIONS AND GAPS IN KNOWLEDGE	166
5.1		EMMISSIONS INVENTORY	166
5.2		CURRENT AND FUTURE EMISSIONS	167

5.3	WASTE STREAMS	167
5.4	BASELINE COMMUNITY HEALTH SURVEY	168
SECTION 6	BASELINE DATA	169
6.1	CLIMATE	169
6.2	GEOLOGY	169
6.3	TRAFFIC	170
6.4	FAUNA AND FLORA	171
6.5	HERITAGE	174
6.6	SURROUNDING LAND-USE AND SENSITIVE RECEPTORS	174
6.7	CLIMATE CHANGE	175
6.8	CURRENT EMISSIONS	176
6.8.1	<i>Dust emissions monitoring</i>	176
6.8.2	<i>Continuous Online Gas Emission Monitoring (Opsis)</i>	176
6.8.3	<i>External monitoring of emissions</i>	177
6.8.4	<i>Current emissions inventory</i>	177
6.8.5	<i>Potential for dioxin and furans at De Hoek</i>	179
6.8.6	<i>Dispersion Modelling for Current Emissions</i>	179
6.9	BASELINE COMMUNITY HEALTH SURVEY	188
6.9.1	<i>Limitations</i>	188
SECTION 7	ALTERNATIVES	190
7.1	TYPES OF SECONDARY MATERIALS	191
7.2	TRANSPORTATION ALTERNATIVES	191
7.2.1	<i>Modes of transport - Road and Rail</i>	191
7.3	TECHNOLOGY ALTERNATIVES	192
7.3.1	<i>Baghouses</i>	192
7.3.2	<i>Methods to increase efficiency of scrubbing effect</i>	192
7.4	NO-GO ALTERNATIVE	193
7.4.1	<i>Incineration vs. Cement Kiln Co-processing</i>	193
7.4.2	<i>Disposal to Landfill versus Cement Kiln Co-processing</i>	195
SECTION 8	PUBLIC PARTICIPATION	197
8.1	PUBLIC PARTICIPATION PERIOD 2 NOVEMBER 2006 – 3 DECEMBER 2006	197
8.1.1	<i>Background information document (BID)</i>	197
8.1.2	<i>Newspaper Advertisement</i>	197
8.1.3	<i>Site Notices</i>	197
8.1.4	<i>Identified Interested and Affected Parties</i>	197
8.1.5	<i>Public Participation Documents</i>	198
8.1.6	<i>Open Day and Registered Interested and Affected Parties</i>	198
8.2	PUBLIC PARTICIPATION PERIOD 2 NOVEMBER 2006 – 3 DECEMBER 2006	199
8.2.1	<i>Background Information Document (BID) and Draft Environmental Impact Report (EIR)</i>	199
8.2.2	<i>Newspaper Advertisement</i>	199
8.2.3	<i>Site Notices</i>	200
8.2.4	<i>Public Participation Documents</i>	201
8.2.5	<i>Open Day and Registered Interested and Affected Parties</i>	202
8.3	REGISTER OF INTERESTED AND AFFECTED PARTIES	202
8.4	ISSUES AND RESPONSE REGISTER	202
SECTION 9	ISSUES IDENTIFICATION	234
9.1	GEOLOGY	234
9.2	TRAFFIC AND TRANSPORTATION	234
9.2.1	<i>Traffic Impact</i>	234
9.2.2	<i>Transportation, Handling and Storage of Hazardous Waste</i>	235
9.3	FAUNA, FLORA AND HERITAGE	235
9.4	CLIMATE CHANGE	235
9.5	GENERATION OF WASTE AND EFFLUENT	236
9.6	SOIL AND SURFACE WATER CONTAMINATION	236
9.7	EMISSIONS	236

9.8	INCIDENTS AND ACCIDENTS	238
9.9	REDUCTION OF WASTE SENT TO LANDFILL	238
9.10	OCCUPATIONAL EXPOSURE TO CEMENT AND CONCRETE	238
SECTION 10	INVESTIGATION OF ISSUES	239
10.1	MASS BALANCES ACROSS THE KILN AND DETERMINATION OF ENVIRONMENTAL RISK ASSESSMENT METHODOLOGY	239
10.2	ASSUMED OUTPUTS AND EMISSIONS FOR ENVIRONMENTAL RISK ASSESSMENT	242
10.3	SPECIALIST STUDIES FOR IMPACTS OF EMISSIONS	243
10.4	POTENTIAL FOR DIOXINS AND FURANS	245
10.5	EMISSIONS DISPERSION MODELLING	246
	10.5.1 Results for Criteria Pollutants	247
10.6	BASELINE COMMUNITY HEALTH SURVEY	255
10.7	COMMUNITY HEALTH RISK ASSESSMENT	255
	10.7.1 Introduction	255
	10.7.2 Findings	255
	10.7.3 Assumptions and Recommendations	258
10.8	ON-SITE STORAGE OF SECONDARY MATERIALS	258
10.9	HAZOP STUDY	258
	10.9.1 Interim HAZOP Conclusions	260
10.10	A REVIEW OF THE WASTE HIERARCHY AND A LIFE CYCLE APPROACH TO DISPOSAL BY CEMENT KILN	260
	10.10.1 Cement kiln disposal in terms of DEAT's Waste Hierarchy	261
	10.10.2 Market Forces	262
	10.10.3 SA Policy and Legislation	263
	10.10.4 Waste Disposal by Cement Kiln – A Comparative Approach	264
	10.10.5 Conclusion from the Life Cycle Assessment on Waste Disposal	265
10.11	PPC EXPERIENCE WITH SECONDARY MATERIALS	265
10.12	AEC SURVEYS & TRIALS	266
	10.12.1 Background	266
	10.12.2 The Guideline Regulation Used for the AEC Studies	266
	10.12.3 Baseline Survey	267
	10.12.4 Test Burn	267
	10.12.5 Trial Burn	267
	10.12.6 Conclusions	269
10.13	XYLENE TRIAL BURN	270
	10.13.1 Background	270
	10.13.2 Regulatory Requirements	270
	10.13.3 Risks Assessment	270
	10.13.4 Emission Results	271
10.14	BACKGROUND TO SPL PROCESSING	272
	10.14.1 Particulate, Fluoride and Cyanide Emissions	273
10.15	SPL HAZARD & OPERABILITY STUDY	274
SECTION 11	TABLE OF IMPACTS AND PROPOSED MITIGATION	276
11.1	INTRODUCTION TO TABLES	277
11.2	IMPACT STATEMENT	285
SECTION 12	CONCLUSIONS	288
12.1	ADVANTAGES OF CEMENT KILN DISPOSAL BY PPC	289
	12.1.1 Regional presence	289
	12.1.2 Cautionary Approach	289
	12.1.3 International trends	289
	12.1.4 Cements kilns more favourable than incinerators and landfills	289
	12.1.5 Elimination and positive use of waste	290
	12.1.6 Process suitability	290
	12.1.7 Inherent gas scrubbing ability	290
	12.1.8 Product safety	290
	12.1.9 Greenhouse gas reduction	291
	12.1.10 Inherent quality assurance and process control	291

	12.1.11 Acceptable community health risk	292
	12.1.12 Liquid effluent	292
12.2	RISKS OF CEMENT KILN DISPOSAL BY PPC	292
	12.2.1 Air emissions	292
	12.2.2 Process Risks	294
	12.2.3 Risks of hazardous waste handling, storage and transport	295
	12.2.4 Variations in compositions of waste streams	295
	12.2.5 Absence of empiric models	295
	12.2.6 Absence of previous experience besides SPL	295
SECTION 13	RECOMMENDATIONS	296
13.1	COMPLIANCE WITH POLICIES	296
13.2	CAUTIONARY APPROACH	296
13.3	TRIAL BURNS	296
13.4	FULL-SCALE PRODUCTION	298
13.5	MONITORING AND MEASUREMENT	299
13.6	EXTERNAL AUDITS AND REPORTING	300
13.7	OTHER AUTHORISATIONS REQUIRED AFTER TRIAL BURNS BUT BEFORE FULL-SCALE PRODUCTION	301
13.8	SAMPLING AND ACCEPTANCE, TRANSPORTATION, HANDLING AND STORAGE OF WASTE STREAMS	301
13.9	HAZOP STUDIES	304
13.10	STAFF TRAINING AND AWARENESS	304
13.11	OCCUPATIONAL HEALTH AND SAFETY	304
13.12	EMERGENCY RESPONSE PLAN	305

LIST OF TABLES

Table 1-1: List of relevant PPC Manufacturing Plants _____	60
Table 1-2: PPC's Plants in South Africa _____	81
Table 3-1: Typical Secondary Fuels in the manufacture of Portland Cement _____	95
Table 3-2: Recent patterns in use of alternative fuels _____	97
Table 3-3: Types of Alternative Fuels (2001) according to the WBCSD _____	97
Table 3-4: Alternative Fuels and Raw Materials in the Japanese Cement Industry (thousand tons) _____	98
Table 3-5: Example Limits on Compounds for Secondary Materials in Cement Kilns _____	99
Table 3-6: Sources of NO _x in a Cement Kiln _____	102
Table 3-7: Metal emissions and Retention for kilns in the US. Note: PPC kilns will have slightly different values and these figures are included for reference purposes only. _____	111
Table 3-8: Typical Heating Values of Secondary Materials _____	116
Table 3-9: Example of metal Concentrations in Portland Cement Extracts _____	122
Table 3-10: Self-Regulated Constituents and Properties of the Secondary Materials and their environmental risks _____	125
Table 3-11: ISO 11014 or ANSIZ400.1.1993 requirements for an MSDS _____	128
Table 3-12: Classification of Hazardous Waste according to SANS 10228 _____	129
Table 3-13: Minimum Requirements for Waste Handling, Storage and Transportation _____	131
Table 3-14: Comparative Emission Limits for Cement Kilns _____	140
Table 4-1: Storage arrangements for Secondary Materials _____	151
Table 4-2: On-site Storage Facilities for each waste stream _____	153
Table 4-3: Feed systems for Secondary Materials _____	155
Table 4-4: Emissions Control equipment at PPC's facilities _____	158
Table 4-5: Waste Streams to be sourced for Trial Burn _____	162
Table 6-1: Stack Monitoring at PPC Production Facilities _____	176
Table 6-2: Stack gas parameters for DHK5 _____	177
Table 6-3: Emissions Inventory for Kiln 5 (Current emissions and limits) _____	178
Table 6-4: Stack gas parameters for DHK6 _____	178
Table 6-5: Emissions Inventory for Kiln 6 (Current emissions and limits) _____	178
Table 7-1: Process Alternatives investigated _____	190
Table 7-2: Comparison of inputs and outputs to a cement kiln used for co-processing and dedicated incinerators _____	194
Table 7-3: Air emission limit values for incineration and co-incineration of waste under Directive 2000/76/EC _____	194
Table 8-1: Issues Register _____	203
Table 9-1: Trip Generation Threshold Value for a Traffic Impact Study _____	234
Table 9-2: Constituents and Properties of the Secondary Materials and their environmental risks _____	237
Table 10-1: Inputs and Outputs from the cement manufacturing process _____	239
Table 10-2: Secondary Materials emission limits _____	242

Table 10-3: Identification of Specialist Studies _____	244
Table 10-4: Summary of exposure levels for gaseous pollutants for future emissions _____	256
Table 10-5: Summary of risk exposure for metalloids, metals and dioxins for future emissions _____	257
Table 10-6: Legislation, policies and principles reviewed _____	263
Table 10-7: Organic substances that composed the waste derived fuel for trial burn _____	268
Table 10-8: Ash, water and elemental compositions of waste derived fuel and coal feed material for trial burn of pitch feed at Jupiter _____	268
Table 10-9: TCDD equivalents and release rates (rounded-off values) for Jupiter trial burn of pitch feed _____	269
Table 10-10: Typical SPL Composition (ALCOA data) _____	273
Table 10-11: SPL Emission Trials 1999-2000 _____	274
Table 11-1: Thresholds of Significance Tables _____	276
Table 11-2: Table of Impacts – Construction Phase _____	278
Table 11-3: Table of Impacts – Operational Phase _____	280
Table 12-1: Production and Environmental Risks as a result of various input components or properties _____	294
Table 13-1: Waste Streams to be sourced for Trial Burn _____	297
Table 13-2: Secondary Materials emission limits _____	298
Table 13-3: Feed systems for Secondary Materials _____	299
Table 13-4: Storage guidelines for specific waste streams _____	303

LIST OF FIGURES

Figure 1-1: The positions of the PPC Manufacturing Plants where the use of secondary materials is proposed. _____	61
Figure 1-2: Aerial photograph of the PPC De Hoek and the Zoutkloof Quarry _____	62
Figure 1-3: Topographical Map showing the PPC De Hoek factory _____	63
Figure 1-4: Photographs of the quarry at Zoutkloof. _____	85
Figure 1-6: Photograph of the De Hoek factory showing the kiln. _____	87
Figure 1-7: Photograph of a preheater at De Hoek. _____	88
Figure 1-8: Kiln reaction profile. _____	89
Figure 1-9: Photograph of cooled Clinker _____	90
Figure 1-10: Flow diagram showing inputs and outputs in the cement manufacturing process _____	91
Figure 3-1: Relationship between CO and Excess Oxygen _____	104
Figure 3-2: Circulation Phenomena _____	107
Figure 3-3: Concentration of Dioxin as a function of Fuel Type _____	114
Figure 3-4: Reduction in overall emission by partial fuel replacement in cement kilns _____	119
Figure 3-5: Waste Management Hierarchy _____	120
Figure 3-6: SHE Control Hierarchy _____	128
Figure 4-1: Example of an Accept-Refuse Chart for SM use _____	142
Figure 4-2: Secondary Materials Sampling and Handling _____	149

Figure 4-3: Secondary Materials Transport Flowchart	150
Figure 4-4: Possible Feed Points for Secondary Material	154
Figure 6-1: Geological conditions	170
Figure 6-2: Map showing the N7 to De Hoek.	171
Figure 6-3: Map showing Veldtype associated with the region	173
Figure 6-4: Map showing Conservation Areas the region	174
Figure 6-5: Map showing the natural heritage sites	174
Figure 6-6: OPSIS instrument installation in the inlet duct to a cement kiln stack	176
Figure 6-7: Average daily PM10 ground level concentrations	182
Figure 6-8: Highest daily NO _x ground level concentrations	183
Figure 6-9: Highest daily SO ₂ ground level concentrations	184
Figure 6-10: Highest daily CO ground level concentrations	185
Figure 6-11: Highest daily HF ground level concentrations	186
Figure 6-12: Highest daily HCl ground level concentrations	187
Figure 10-1: Mass Flow Scheme using Secondary Materials in Cement Manufacture	240
Figure 10-2: Relationship between secondary materials input and possible downstream receptors	244
Figure 10-14: Roles in the Waste hierarchy	261
Figure 10-15: Waste Management Costs for Plastics	262
Figure 10-16: Waste Management Costs for Tyres	263
Figure 10-17: Xylene Trial burn: SK8 VOC Measurements by external monitoring group (Levego)	272

GLOSSARY OF TERMS

Aggregates	Crushed stone, sand and gravel. Concrete and mortar are made by using aggregates mixed with cement and water.
Absorbent	Solid material that removes components from a gas or liquid.
Alkaline conditions	Condition of high pH where acidic compounds could be neutralized or acid-base reactions can take place.
Bag filter	Dust collection device using fabric filter bags for cleaning exhaust gas from a process plant.
Baseline emission levels	The historical or normal emission level of an entity in a process without changes to input material or changes to the process.
Best practice	Internationally recognized, most efficient / effective techniques applied in manufacturing and production processes.
Biomass	A material of biological nature that is continuously generated by industrial processes or human activity.
Blending silo	Stores and blends finely ground materials
Bypass system	Arrangement whereby material or gas flow is directed around the normal process equipment, and not through it.
By-products	By-products are materials which are co-produced in manufacturing processes. Fly ash from coal combustion in electricity generation, and blast furnace slag from the production of iron are two examples.
Calciner	See "Pre-calciner"
Carbonaceous Spent Pot Lining (CSPL)	The carbonaceous portion of the SPL is the carbon lining that forms the cathode material that is used in the aluminium smelting process.
Carcinogens	Cancer causing substance or agent.
Cement (Portland Cement)	Hydraulic cement (that not only hardens by reacting with water but also forms a water-resistant product) produced by grinding clinker, (essentially calcium silicates), together with about 5% gypsum (calcium Sulphate, which is added to regulate the cement setting time). The name "Portland cement" is derived from the similarity in colour of cement after setting to the grey slate from Portland, UK.
Clinker	Nodular to powdery material produced in a rotary kiln by heating a blended, finely ground mixture of limestone (or calcium carbonate), shale (or other suitable material for silica and alumina), and a source of iron oxide to a temperature of approximately 1450°C
Coal mill	The plant required to dry and grind coal to produce a fuel for kiln firing.
Combustion	Reaction of a fuel with oxygen
Combustion efficiency	Indication of completeness of combustion of organic material (containing carbon) to carbon dioxide (CO ₂)

Condensation	Phase change of vapour to liquid
Cooler	Cools the clinker discharged from a cement kiln (at about 1100°C) to typically less than 200°C prior to transport to storage.
Cooler – Grate type	Cooling is achieved by cross-flow air blown through a clinker layer travelling slowly on a reciprocating grate which consists of perforated plates.
Cooler – satellite type	Nine to eleven tubes arranged peripherally at the discharge end of the rotary kiln. Hot clinker enters the tubes through inlet ports and passes through the tubes in counter current flow to cooling air. Also called a planetary cooler.
Co-processing	Utilization of alternative fuel and raw materials for the purpose of energy and resource recovery. Co-processing in cement manufacturing means substituting scarce primary energy and virgin raw materials with waste materials.
Counter current	Solid material and gas flowing in opposite directions. In all kiln systems the solid material moves counter current to the hot combustion gases.
“De novo” effect	The reformation of dioxins and furans is known to occur by “de novo” synthesis within the window of cooling from 450 to 200° C.
Effluent	A liquid waste stream.
Excess air	Ensures complete combustion of fuel due to the presence of excess oxygen (O ₂)
Extender (Pozzolanic)	See Pozzolan.
Extender (Filler)	See Non-Deleterious Materials
Flue gas	Exhaust gas from a combustion process.
Fly ash	A by-product from coal-fired power stations. Fly ash can be added to Portland cement as an extender or NDM (Non-Deleterious Materials)
Fossil fuel	A general term for combustible deposits of carbon in reduced (organic) form and of biological origin, including coal, oil, natural gas, and oil shale.
Greenhouse gases	Gases in the earth’s lower atmosphere that may contribute to global warming, of which CO ₂ is a major component
Hazardous Waste	A material defined by regulation or legislation as flammable, explosive, corrosive or toxic, therefore requiring special handling or disposal
Heavy metals	All metals heavier than Titanium (4.51 g/cm ³) are termed heavy metals. The heavy metals make up a small proportion of the materials in the earth’s crust. Not all heavy metals are toxic and not all toxic heavy metals have the same toxicity.
Hydrocarbons	Chemical compounds consisting of the elements carbon and hydrogen used as building blocks in their structure

Incinerator	Plant used for the combustion of waste materials to yield a non-combustible residue or ash and exhaust gases, such as carbon dioxide and water.
Kiln dust	Particulate, solid material entrained in the exhaust gas from a cement kiln.
Kiln feed	Homogenised raw meal added to a rotary cement kiln at a controlled rate.
Leachate	Contaminated water or a solution with the potential to cause pollution, if the liquid is permitted to percolate through soil to ground water.
Lepol kiln	A kiln in which the feed is preheated on a horizontal travelling grate before entering the kiln.
Life cycle	Industrial processes involved in production including upstream extraction, manufacturing, distribution, use, and re-use or disposal of resulting waste materials
Limestone	Rock consisting essentially of carbonates with the most important constituents being calcite (CaCO_3).
Mineral additions	In blended (or “composite”) cements, a portion of the cement consists of materials (mineral additions) originating from natural or industrial sources such as blast furnace slag
Non-Deleterious Materials	Materials that can be added at the clinker grinding stage that do not have any negative effects on the cement performance. There are limits to the quantities of extenders that can be added to the cements based on the relevant SANS specification (SANS 50197).
Organic material	Chemical compound from natural sources with carbon as its core element
Oxidizing conditions	High oxygen content allowing complete oxidation of compounds (see excess air)
Physico-chemical absorption	Absorption due to chemical reaction and physical inclusion
Planetary Clinker Cooler	Refer to Cooler – satellite type
Pozzolan	A material that, although itself not cementitious, contains silica (and alumina) in a reactive form and is able to combine with lime in the presence of water to form compounds with cementitious properties.
Pre-calciner	A fluidized reaction vessel located above the feed end of the kiln which enables preheated kiln feed to be calcined before entering the kiln.
Preheater	Before entering the kiln, the kiln feed is preheated by suspension in the hot kiln exhaust gas stream in several cyclone stages (from 1 to 6) arranged vertically. The cyclone tower is known as the preheater.
Quarrying	Extracting raw materials from the earth.
Raw meal	Raw materials that are dried and ground in defined and well-controlled proportions in a raw mill

Raw mill	The plant for proportioning, drying and grinding the raw materials used for cement production.
Reducing conditions	Low oxygen content not allowing complete oxidation of compounds by oxygen
Refractory Spent pot lining (RSPL)	Waste refractory bricks which have been used for thermal protection of the pots at an aluminium smelter
Residues	Unwanted materials left by a manufacturing process.
Retention time	Time taken for material to pass through a process at the optimal operating conditions.
Rotary kiln	An inclined rotating steel cylinder lined with refractory bricks used to produce cement clinker.
Rotary kiln burner	Positioned at the kiln discharge end (firing end) to introduce fuel to the kiln process.
Scrubber	Equipment to remove impurities from a gas stream using a wet or dry process.
Secondary materials	Waste or by-products used in cement manufacturing as alternatives to fossil fuels and natural raw materials.
Shale	An argillaceous sedimentary rock
Sintering	Formation of clinker minerals in the cement kiln.
Stack	A chimney that exhausts gas from various stages in the cement manufacturing process.
Sustainable development	The ability of the present generation to continually meet its needs without compromising the ability of future generations to meet theirs.
Trace elements	Chemical elements present in minute quantities.
Turbulence	Condition under which intense and aggressive mixing and contact of materials occurs.
Volatility	Tendency of a chemical compound to form vapour under a given set of conditions.
Waste	An undesirable or superfluous by-product, emission, or residue of a process or activity which has been discarded, accumulated or stored for the purpose of further use by another process.

ABBREVIATIONS

ACMP	Association of Cementitious Material Producers
AFR	Alternative fuels and raw materials
ANSI	American National Standards Institute
APPA	Atmospheric Pollution Prevention Act (No 45 of 1965)
BAT	Best Available Techniques
BCHS	Baseline Community Health Survey
BID	Background Information Document
BEP	Best Environmental Practice
CAPCO	Chief Air Pollution Control Officer
CHRA	Community Health Risk Assessment
DEAT	Department of Environmental Affairs and Tourism
DRE	Destruction and Removal Efficiency
DWAF	Department of Water Affairs and Forestry
EA	Environmental Assessment
EAP	Environmental Assessment Practitioner
EC	European Community
ECA	Environmental Conservation Act (Act 73 of 1989)
EIA	Environmental Impact Assessment
EMP	Environmental Management Plan
EPA	Environmental Protection Agency
ESP	Electrostatic Precipitator
ETR	Environmental technical Review
EU	European Union
FCC	Fluidized catalyst cracking
g	Gram
HAZOP	Hazard and operability study
HCS	Hazardous Chemical Substances
HM	Heavy metals
I&APs	Interested and Affected Parties
IDP	Integrated Development Plan
ISO	International Standards Organization
kg	Kilogram
kJ	Kilojoule

kPa	Kilopascal
LCA	Life Cycle Assessment
LOI	Loss on ignition
m ³	Cubic meter
MES	Marsh Environmental Services
MHSA	Mine Health and Safety Act (No 29 of 1996)
MJ	Megajoule
MSDS	Material safety and data sheet
NDM	Non-Deleterious Materials
NEMA	National Environmental Management Act (Act 107 of 1998)
ng	Nanogram (1 x 10 ⁻⁹ grams)
Nm ³	Normal or standard volume under standard conditions (0°C & 1.01 bar)
OEL	Occupational exposure limits
OH&S	Occupational Health and Safety
OSHAct	Occupational health and safety act (No 85 of 1993)
OSHAS	Occupational health and safety management systems (British)
pH	Acidity scale 1 to 14
PM10	Particulate matter smaller than 10 µm
POPs	Persistent organic pollutants
PoSS	Plan of Study for Scoping
ppb	Parts per billion
PPC	Pretoria Portland Cement
PPE	Personal protective equipment
PPM	Public Participation Meeting
ppm	Parts per million
PPP	Public Participation Process
RDF	Refuse derived fuels
SANS	South African National Standard
SHE	Safety, Health & Environment
SHEQ	Safety, Health, Environment & Quality
SK1	PPC equipment terminology (Plant & Kiln number, S=Slurry; PE=Port Elizabeth; DB=Dwaalboom; H=Hercules; D=De Hoek, K=Kiln)
SM	Secondary materials
SP	Suspension (or cyclone) preheater kiln
PC	Calciner kiln (which also has a cyclone preheater)
SPL	Spent Pot Lining

SR	Scoping Report
T	Temperature
TEQ	Toxicity Equivalent
TCLP	Toxicity Characteristic Leaching Procedure
TOC	Total organic carbon
UNEP	United Nations Environment Program
VOC	Volatile organic compound
WBCSD	World Business Council for Sustainable Development
WC DEADP	Western Cape Department of Environmental Affairs and Development Planning
WDF	Waste derived fuel
WUL	Water use Licence
µg	Microgram

S=Slurry; PE=Port Elizabeth; DB=Dwaalboom; H=Hercules; D=De Hoek.

CHEMICAL ABBREVIATIONS

Ag	Silver
Al ₂ O ₃	Aluminium oxide
As	Arsenic
Ba	Barium
Be	Beryllium
BTX	Benzene, toluene, xylene
C ₆ H ₆	Benzene
CaCO ₃	Calcium carbonate
CaO	Calcium oxide
CaSO ₄	Calcium sulphate
CaSO ₄ .2H ₂ O	Gypsum
Cd	Cadmium
CFCs	Chlorofluorocarbons
CH ₄	Methane
CO	Carbon monoxide
Co	Cobalt
CO ₂	Carbon dioxide
Cr	Chromium
Cu	Copper
F	Fluoride
Fe ₂ O ₃	Iron oxide
FeS ₂	Iron sulphide
H ₂ O	Water
HCB	Hexachlorobenzene
HCl	Hydrogen chloride (hydrochloric acid)
HF	Hydrogen fluoride (hydrofluoric acid)
Hg	Mercury
K ₂ O	Potassium oxide
MgO	Magnesium oxide
Mn	Manganese
Mn ₂ O ₃	Manganese trioxide
NH ₃	Ammonia
N ₂	Nitrogen

Na ₂ O	Sodium oxide
Na ₂ SO ₄	Sodium sulphate
Ni	Nickel
NO _x	Nitrogen oxides
O ₂	Oxygen
P ₂ O ₅	Phosphorus pentoxide
PAH	Polyaromatic hydrocarbons
Pb	Lead
PCBs	Polychlorinated biphenyls
PCDDs	Polychlorinated dibenzodioxins
PCDFs	Polychlorinated dibenzofurans
Pd	Palladium
Pt	Platinum
Rh	Rhodium
Sb	Antimony
Se	Selenium
SiO ₂	Silicon dioxide
Sn	Tin
SO ₂	Sulphur dioxide
SO ₃	Sulphur trioxide
SO _x	Sulphur oxides
TCE	Trichloroethylene
TCM	Tetra-chloromethane
Te	Tellurium
Ti	Titanium
TiO ₂	Titanium dioxide
Tl	Thallium
V	Vanadium
Zn	Zinc
°C	Degrees Celcius