

## TABLE OF CONTENTS

<b>SECTION 1</b>	<b>INTRODUCTION</b>	<b>41</b>
1.1	A BRIEF DESCRIPTION OF THE PROPOSED ACTIVITY	41
1.2	PPC DWAALBOOM	43
1.3	PPC DWAALBOOM CEMENT MANUFACTURING PLANT	43
1.4	THE LEGAL FRAMEWORK	45
1.4.1	<i>Plan of Study for Scoping</i>	45
1.4.2	<i>Provisions of the approval of the Plan of Study for Scoping</i>	47
1.4.3	<i>Process background and programme</i>	48
1.5	SCOPING REPORT	49
1.5.1	<i>Methodology</i>	49
1.5.2	<i>Specialist Studies</i>	49
1.5.3	<i>General Terms of Reference</i>	50
1.5.4	<i>The Environmental Consultant</i>	50
1.6	THE PROPONENT	51
1.6.1	<i>History of PPC</i>	51
1.7	PROONENT'S MOTIVATION AND OVERALL COMMITMENT FOR THE USE OF SECONDARY MATERIALS	52
<b>SECTION 2</b>	<b>THE CEMENT MANUFACTURING PROCESS</b>	<b>55</b>
2.1	A DETAILED DESCRIPTION OF THE CEMENT MAKING PROCESS AT DWAALBOOM	55
2.1.1	<i>Primary Raw Materials</i>	55
2.1.2	<i>Secondary Raw Materials</i>	58
2.1.3	<i>Clinker burning</i>	58
2.1.4	<i>Clinker</i>	60
2.1.5	<i>Milling and Final Product (Cement)</i>	61
2.1.6	<i>Cement dispatch</i>	61
2.1.7	<i>Summary of inputs and outputs</i>	61
<b>SECTION 3</b>	<b>ENVIRONMENTAL ASPECTS OF SECONDARY MATERIALS CO-PROCESSING IN THE MAKING OF CEMENT</b>	<b>63</b>
3.1	INTRODUCTION TO SECONDARY MATERIALS CO-PROCESSING	63
3.1.1	<i>Why is the Cement Kiln Suitable for Co-Processing of Secondary Materials?</i>	63
3.1.2	<i>International use of Secondary Materials</i>	64
3.1.3	<i>International Trends</i>	66
3.1.4	<i>Specified limits on Secondary Material Inputs</i>	69
3.1.5	<i>Use of Secondary Materials at PPC</i>	70
3.2	EMISSIONS TO ATMOSPHERE	70
3.2.1	<i>Inherent Combustion Gas Cleaning Capability</i>	71
3.2.2	<i>Nitrogen oxides (NO<sub>x</sub>) formation</i>	71
3.2.3	<i>Carbon Monoxide (CO) formation</i>	73
3.2.4	<i>Volatile Components</i>	74
3.2.5	<i>Organic Compounds</i>	74
3.2.6	<i>Sulphur Compounds</i>	75
3.2.7	<i>Behaviour of Volatile Components</i>	76
3.2.8	<i>Evaporation and condensation in the kiln system (circulation)</i>	77
3.2.9	<i>Affinity between the Volatile Components</i>	77
3.2.10	<i>Potential for Evaporation</i>	78
3.2.11	<i>Molecular Ratio of Sulphur and Alkalis</i>	78
3.2.12	<i>Sulphur Dioxide (SO<sub>2</sub>) entrapment in the preheater system</i>	78
3.2.13	<i>Ammonia (NH<sub>3</sub>)</i>	79
3.2.14	<i>Halogens (Cl and F)</i>	79
3.2.15	<i>Metals</i>	79
3.2.16	<i>Dioxins and Furans</i>	80
3.2.17	<i>Dust</i>	84
3.3	CONSERVATION OF NATURAL RESOURCES	85

<b>3.4</b>	LIQUID EFFLUENT	86
<b>3.5</b>	POTENTIAL FOR SURFACE WATER, SOIL AND GROUNDWATER CONTAMINATION DURING TRANSPORTATION OF HAZARDOUS WASTES	86
<b>3.6</b>	POTENTIAL FOR SURFACE WATER, SOIL AND GROUNDWATER CONTAMINATION ON-SITE	87
<b>3.7</b>	GENERATION OF SOLID WASTE	87
<b>3.8</b>	GREENHOUSE GAS REDUCTION	88
<b>3.9</b>	REDUCTION OF WASTE SENT TO LANDFILL	88
<b>3.10</b>	POTENTIAL IMPACT ON WATER QUALITY DUE TO USE OF CEMENT MADE FROM SECONDARY MATERIALS INCLUDING PRODUCT LEACHING	89
<b>3.11</b>	PROCESS CONTROL AND KILN STABILITY	91
<b>3.12</b>	SELF-REGULATION AND QUALITY ASSURANCE	94
<b>3.13</b>	LEGISLATION APPLICABLE TO THE USE OF SECONDARY MATERIALS	95
	3.13.1 <i>Occupational Health and Safety Act (Act 85 of 1993)</i>	95
	3.13.2 <i>Environment Conservation Act, 1989 (Act 73 of 1989), National Water Act, 1998 (Act 36 of 1998) and the Water Services Act, 1997 (Act 108 of 1997)</i>	97
	3.13.3 <i>Minimum Requirements for the Handling, Classification and Disposal of Hazardous Waste (DWAF, 2nd edition, 1998)</i>	98
	3.13.4 <i>CAPCO Limits and Design Criteria</i>	99
<b>3.14</b>	INTERNATIONAL EMISSIONS LIMITS	102
<b>SECTION 4 PPC'S SECONDARY MATERIALS CO-PROCESSING PROGRAMME</b>		<b>104</b>
<b>4.1</b>	SAMPLING AND ACCEPTANCE OF SECONDARY MATERIALS PRIOR TO PROCESSING	104
	4.1.1 <i>Introduction</i>	104
	4.1.2 <i>Initial Screening</i>	106
	4.1.3 <i>Waste Identification Analysis</i>	106
	4.1.4 <i>Sampling Protocols</i>	107
	4.1.5 <i>Suitability for the Cement Kiln (Desktop Study)</i>	108
	4.1.6 <i>Plant Trial</i>	108
	4.1.7 <i>Implementation</i>	108
	4.1.8 <i>Regular Cross Check</i>	110
	4.1.9 <i>External verification, auditing and reporting</i>	111
<b>4.2</b>	PHYSICAL OPERATION OF SECONDARY MATERIALS PROCESSING	114
	4.2.1 <i>Collection from Generator and Transport to site</i>	114
	4.2.2 <i>On-site storage</i>	115
	4.2.3 <i>Feed to the kiln</i>	117
<b>4.3</b>	SELECTION OF INJECTION POINT	119
<b>4.4</b>	PROCESS MONITORING DURING OPERATION	120
<b>4.5</b>	EMISSIONS CONTROL AT PPC'S OPERATIONS	120
<b>4.6</b>	EMISSIONS MONITORING DURING OPERATION	121
<b>4.7</b>	AUDITING AND REPORTING DURING OPERATION	122
<b>4.8</b>	EMERGENCY PREPAREDNESS AND RESPONSE	123
<b>4.9</b>	HEALTH AND SAFETY	123
<b>4.10</b>	EMPLOYEE TRAINING	124
<b>4.11</b>	TRIAL BURN	124
	4.11.1 <i>Schedule of trial burns</i>	124
	4.11.2 <i>Waste to be sourced</i>	125
	4.11.3 <i>Blending of Wastes for Trial Burn</i>	125
	4.11.4 <i>Storage and Feed to Kiln</i>	126
	4.11.5 <i>Process Monitoring</i>	127
	4.11.6 <i>Independent audit</i>	127
	4.11.7 <i>Emissions Monitoring and Reporting</i>	127
<b>SECTION 5 BASELINE DATA</b>		<b>129</b>
<b>5.1</b>	CLIMATE	129
	5.1.1 <i>Rainfall and Temperature</i>	129
	5.1.2 <i>Wind Direction</i>	129
<b>5.2</b>	GEOLOGY	130
<b>5.3</b>	TRAFFIC	131
<b>5.4</b>	FAUNA AND FLORA	132

<b>5.5</b>	SURROUNDING LAND-USE _____	133
<b>5.6</b>	CURRENT EMISSIONS _____	133
5.6.1	<i>Dust emissions monitoring</i> _____	133
5.6.2	<i>Continuous Online Gas Emission Monitoring (Opsis)</i> _____	134
5.6.3	<i>External monitoring of emissions</i> _____	135
5.6.4	<i>Current emissions inventory</i> _____	135
5.6.5	<i>Dispersion Modelling for Current Emissions</i> _____	137
<b>5.7</b>	BASELINE COMMUNITY HEALTH SURVEY _____	147
5.7.1	<i>Limitations</i> _____	147
<b>SECTION 6</b>	<b>ALTERNATIVES</b> _____	<b>149</b>
<b>6.1</b>	TYPES OF SECONDARY MATERIALS _____	149
<b>6.2</b>	INCINERATION VS. CEMENT KILN CO-PROCESSING _____	150
<b>6.3</b>	DISPOSAL TO LANDFILL VERSUS CEMENT KILN CO-PROCESSING _____	152
<b>SECTION 7</b>	<b>PUBLIC PARTICIPATION</b> _____	<b>154</b>
<b>7.1</b>	PUBLIC PARTICIPATION PERIOD _____	154
7.1.1	<i>Background information document (BID)</i> _____	154
7.1.2	<i>Newspaper Advertisement</i> _____	154
7.1.3	<i>Site Notice</i> _____	155
7.1.4	<i>Identified Interested and Affected Parties</i> _____	155
7.1.5	<i>Public Participation Documents</i> _____	156
7.1.6	<i>Open Day and Registered Interested and Affected Parties</i> _____	156
<b>7.2</b>	REGISTER OF INTERESTED AND AFFECTED PARTIES _____	159
<b>7.3</b>	ISSUES AND RESPONSE REGISTER _____	160
<b>SECTION 8</b>	<b>ISSUES IDENTIFICATION</b> _____	<b>183</b>
<b>8.1</b>	GEOLOGY _____	184
<b>8.2</b>	TRAFFIC _____	184
<b>8.3</b>	FAUNA, FLORA AND HERITAGE _____	185
<b>8.4</b>	GENERATION OF WASTE AND EFFLUENT _____	185
<b>8.5</b>	EMISSIONS _____	185
<b>8.6</b>	INCIDENTS AND ACCIDENTS _____	186
<b>8.7</b>	REDUCTION OF WASTE SENT TO LANDFILL _____	186
<b>8.8</b>	OCCUPATIONAL EXPOSURE TO CEMENT AND CONCRETE _____	186
<b>SECTION 9</b>	<b>INVESTIGATION OF ISSUES</b> _____	<b>188</b>
<b>9.1</b>	MASS BALANCES ACROSS THE KILN AND DETERMINATION OF ENVIRONMENTAL RISK ASSESSMENT METHODOLOGY _____	188
<b>9.2</b>	ASSUMED OUTPUTS AND EMISSIONS FOR ENVIRONMENTAL RISK ASSESSMENT _____	190
<b>9.3</b>	SPECIALIST STUDIES FOR IMPACTS OF EMISSIONS _____	192
<b>9.4</b>	EMISSIONS DISPERSION MODELLING _____	193
9.4.1	<i>Results for Criteria Pollutants</i> _____	194
<b>9.5</b>	COMMUNITY HEALTH RISK ASSESSMENT _____	209
9.5.1	<i>Introduction</i> _____	209
9.5.2	<i>Findings</i> _____	209
9.5.3	<i>Assumptions and Recommendations</i> _____	211
<b>9.6</b>	HAZOP STUDY _____	211
9.6.1	<i>Interim HAZOP Conclusions</i> _____	213
<b>9.7</b>	A REVIEW OF THE WASTE HIERARCHY AND A LIFE CYCLE APPROACH TO DISPOSAL BY CEMENT KILN _____	213
9.7.1	<i>Cement kiln disposal in terms of DEAT's Waste Hierarchy</i> _____	214
9.7.2	<i>Market Forces</i> _____	215
9.7.3	<i>SA Policy and Legislation</i> _____	216
9.7.4	<i>Waste Disposal by Cement Kiln – A Comparative Approach</i> _____	216
9.7.5	<i>Conclusion from the Life Cycle Assessment on Waste Disposal</i> _____	217
<b>9.8</b>	PPC EXPERIENCE WITH SECONDARY MATERIALS _____	218
<b>9.9</b>	AEC SURVEYS & TRIALS _____	218
9.9.1	<i>Background</i> _____	218

9.9.2	<i>The Guideline Regulation Used for the AEC Studies</i>	218
9.9.3	<i>Baseline Survey</i>	219
9.9.4	<i>Test Burn</i>	219
9.9.5	<i>Trial Burn</i>	219
9.9.6	<i>Conclusions</i>	221
<b>9.10</b>	<b>XYLENE TRIAL BURN</b>	<b>222</b>
9.10.1	<i>Background</i>	222
9.10.2	<i>Regulatory Requirements</i>	222
9.10.3	<i>Risks Assessment</i>	222
9.10.4	<i>Emission Results</i>	223
<b>9.11</b>	<b>BACKGROUND TO SPL PROCESSING</b>	<b>224</b>
9.11.1	<i>Particulate, Fluoride and Cyanide Emissions'</i>	225
<b>9.12</b>	<b>SPL HAZARD &amp; OPERABILITY STUDY</b>	<b>226</b>
<b>SECTION 10</b>	<b>TABLE OF IMPACTS AND PROPOSED MITIGATION</b>	<b>228</b>
<b>10.1</b>	<b>INTRODUCTION TO TABLES</b>	<b>229</b>
<b>10.2</b>	<b>IMPACT STATEMENT</b>	<b>236</b>
<b>SECTION 11</b>	<b>CONCLUSIONS</b>	<b>238</b>
<b>11.1</b>	<b>ADVANTAGES OF CEMENT KILN DISPOSAL BY PPC</b>	<b>238</b>
11.1.1	<i>Regional presence</i>	238
11.1.2	<i>Cautionary Approach</i>	239
11.1.3	<i>International trends</i>	239
11.1.4	<i>Cements kilns more favourable than incinerators and landfills</i>	239
11.1.5	<i>Elimination and positive use of waste</i>	239
11.1.6	<i>Process suitability</i>	239
11.1.7	<i>Inherent gas scrubbing ability</i>	240
11.1.8	<i>Product safety</i>	240
11.1.9	<i>Greenhouse gas reduction</i>	240
11.1.10	<i>Inherent quality assurance and process control</i>	241
11.1.11	<i>Acceptable community health risk</i>	241
11.1.12	<i>Liquid effluent</i>	241
<b>11.2</b>	<b>RISKS OF CEMENT KILN DISPOSAL BY PPC</b>	<b>241</b>
11.2.1	<i>Air emissions</i>	241
11.2.2	<i>Process Risks</i>	243
11.2.3	<i>Risks of hazardous waste handling, storage and transport</i>	244
11.2.4	<i>Variations in compositions of waste streams</i>	244
11.2.5	<i>Absence of empiric models</i>	244
11.2.6	<i>Absence of previous experience besides SPL</i>	244
<b>SECTION 12</b>	<b>RECOMMENDATIONS</b>	<b>245</b>
<b>12.1</b>	<b>COMPLIANCE WITH POLICIES</b>	<b>245</b>
<b>12.2</b>	<b>CAUTIONARY APPROACH</b>	<b>245</b>
<b>12.3</b>	<b>TRIAL BURNS</b>	<b>245</b>
<b>12.4</b>	<b>FULL-SCALE PRODUCTION</b>	<b>247</b>
<b>12.5</b>	<b>MONITORING AND MEASUREMENT</b>	<b>248</b>
<b>12.6</b>	<b>EXTERNAL AUDITS AND REPORTING</b>	<b>249</b>
<b>12.7</b>	<b>OTHER AUTHORISATIONS REQUIRED AFTER TRIAL BURNS BUT BEFORE FULL-SCALE PRODUCTION</b>	<b>250</b>
<b>12.8</b>	<b>SAMPLING AND ACCEPTANCE, TRANSPORTATION, HANDLING AND STORAGE OF WASTE STREAMS</b>	<b>250</b>
<b>12.9</b>	<b>HAZOP STUDIES</b>	<b>253</b>
<b>12.10</b>	<b>STAFF TRAINING AND AWARENESS</b>	<b>253</b>
<b>12.11</b>	<b>OCCUPATIONAL HEALTH AND SAFETY</b>	<b>253</b>
<b>12.12</b>	<b>EMERGENCY RESPONSE PLAN</b>	<b>254</b>

## LIST OF TABLES

Table 1-1:	List of relevant PPC Manufacturing Plants	42
Table 1-2:	Schedule included in the PoSS	48
Table 1-3:	PPC's Plants in South Africa	51
Table 3-1:	Typical Secondary Fuels in the manufacture of Portland Cement	66
Table 3-2:	Recent patterns in use of alternative fuels	67
Table 3-3:	Types of Alternative Fuels (2001) according to the WBCSD	68
Table 3-4:	Alternative Fuels and Raw Materials in the Japanese Cement Industry (thousand tons)	68
Table 3-5:	Example Limits on Compounds for Secondary Materials in Cement Kilns	69
Table 3-6:	Sources of NO <sub>x</sub> in a Cement Kiln	72
Table 3-7:	Metal emissions and Retention for kilns in the US. Note: PPC kilns will have slightly different values and these figures are included for reference purposes only.	80
Table 3-8:	Typical Heating Values of Secondary Materials	86
Table 3-9:	Metal Concentrations in Portland Cement Extracts	91
Table 3-10:	Self-Regulated Constituents and Properties of the Secondary Materials and their environmental risks	94
Table 3-11:	ISO 11014 or ANSIZ400.1.1993 requirements for an MSDS	96
Table 3-12:	Classification of Hazardous Waste according to SANS 10228	97
Table 3-13:	Minimum Requirements for Waste Handling, Storage and Transportation	98
Table 3-14:	Comparative Emission Limits for Cement Kilns	102
Table 4-1:	Storage arrangements for Secondary Materials	114
Table 4-2:	On-site Storage Facilities for each waste stream	116
Table 4-3:	Feed systems for Secondary Materials	118
Table 4-4:	Emissions Control equipment at PPC's facilities	121
Table 4-5:	Waste Streams to be sourced for Trial Burn	125
Table 5-1:	Stack Monitoring at PPC Production Facilities	134
Table 5-2:	Stack gas parameters	135
Table 5-3:	Emissions Inventory for Kiln 1 (Current emissions and limits)	136
Table 5-4:	Stack gas parameters	136
Table 5-5:	Emissions Inventory for Kiln 2	137
Table 6-1:	Process Alternatives investigated	149
Table 6-2:	Comparison of inputs and outputs to a cement kiln used for co-processing and dedicated incinerators	151
Table 6-3:	Air emission limit values for incineration and co-incineration of waste under Directive 2000/76/EC	152
Table 7-1:	Table showing the location and languages of site notices placed in and around the plant.	157
Table 7-2:	Issues and Response Register	161
Table 8-1:	Trip Generation Threshold Value for a Traffic Impact Study	184
Table 8-2:	Constituents and Properties of the Secondary Materials and their environmental risks	186
Table 9-1:	Inputs and Outputs from the cement manufacturing process	188
Table 9-2:	Secondary Materials emission limits	191
Table 9-3:	Identification of Specialist Studies	193
Table 9-4:	Summary of exposure levels for gaseous pollutants for future emissions	210
Table 9-5:	Summary of risk exposure for metalloids, metals and dioxins for future emissions	210

<i>Table 9-6: Legislation, policies and principles reviewed</i>	216
<i>Table 9-7: Organic substances that composed the waste derived fuel for trial burn</i>	220
<i>Table 9-8: Ash, water and elemental compositions of waste derived fuel and coal feed material for trial burn of pitch feed at Jupiter</i>	220
<i>Table 9-9: TCDD equivalents and release rates (rounded-off values) for Jupiter trial burn of pitch feed</i>	221
<i>Table 9-10: Typical SPL Composition (ALCOA data)</i>	225
<i>Table 9-11: SPL Emission Trials 1999-2000</i>	226
<i>Table 10-1: Thresholds of Significance Tables</i>	228
<i>Table 10-2: Table of Impacts – Construction Phase</i>	230
<i>Table 10-3: Table of Impacts – Operational Phase</i>	232
<i>Table 11-1: Production and Environmental Risks as a result of various input components or properties</i>	243
<i>Table 12-1: Secondary Materials emission limits</i>	247
<i>Table 12-2: Feed systems for Secondary Materials</i>	248
<i>Table 12-3: Storage guidelines for specific waste streams</i>	252

## LIST OF FIGURES

Figure 1-1: The positions of the PPC Manufacturing Plants where the use of secondary materials is proposed.	43
Figure 1-2: Aerial photograph of the PPC Dwaalboom Manufacturing Plant	44
Figure 1-3: Aerial photograph of the future PPC Dwaalboom Manufacturing Plant, once construction has been completed; the positions of each kiln are indicated in red	44
Figure 2-1: Aerial view of the two quarries at Dwaalboom, and the crusher	55
Figure 2-2: Generic process flow diagram of the cement manufacturing process.	56
Figure 2-3: Aerial photograph of the limestone stockpiles at Dwaalboom, indicated in red. At the quarry, the limestone is crushed to particles approximately 25mm in size and stored on stockpiles, where the material is homogenised prior to milling.	57
Figure 2-4: Photographs of the stockpiling of limestone at Dwaalboom (A), and the circular reclaimer (B)	57
Figure 2-5: Photograph of the existing kiln at Dwaalboom; the raw meal silo is visible in the background	58
Figure 2-6: Photograph of the 5-stage preheater of Kiln 1 at Dwaalboom. The raw meal silo is located to the left of the preheater.	59
Figure 2-7: Kiln reaction profile for long dry kiln without calciner.	60
Figure 2-8: Photograph of cooled Clinker.	61
Figure 2-9: Flow diagram showing inputs and outputs in the cement manufacturing process	62
Figure 3-1: Relationship between CO and Excess Oxygen	74
Figure 3-2: Circulation Phenomena	77
Figure 3-3: Concentration of Dioxin as a function of Fuel Type	83
Figure 3-4: PCCD/F in Clean Gas as function of Cl Input for kiln in Austria	84
Figure 3-5: Reduction in overall emission by partial fuel replacement in cement kilns	88
Figure 3-6: Waste Management Hierarchy	89
Figure 3-7: SHE Control Hierarchy	96
Figure 4-1: Example of an Accept-Refuse Chart for SM use	105
Figure 4-2: Secondary Materials Sampling and Handling	112
Figure 4-3: Secondary Materials Transport Flowchart	113
Figure 4-4: Possible Feed Points for Secondary Material	117
Figure 5-1: Period-average, daytime and night-time wind roses depicting the wind profile – Thabazimbi Station (Period Jan 2001 – Nov 2006)	129
Figure 5-2: Seasonal average wind roses for Thabazimbi (2001 – 2006)	130
Figure 5-3: Geological conditions	131
Figure 5-4: Map showing major transport routes around Dwaalboom	132
Figure 5-5: Map showing communities in the region.	133
Figure 5-6: OPSIS instrument installation in the inlet duct to a cement kiln stack	134
Figure 5-7: Average daily PM10 ground level concentrations	140
Figure 5-8: Average daily TSP dust fallout (mg/m <sup>2</sup> /day)	141
Figure 5-9: Highest daily NO <sub>x</sub> ground level concentrations	142
Figure 5-10: Highest daily SO <sub>2</sub> ground level concentrations	143
Figure 5-11: Highest daily CO ground level concentrations	144
Figure 5-12: Highest daily HF ground level concentrations	145
Figure 5-13: Highest daily HCl ground level concentrations	146
Figure 7-1: Copy of the Afrikaans (A) and English (B) advertisements placed in Die Kwévoël	155

<i>Figure 7-2: Image of the (A) English and (B) Afrikaans advertisements placed in Die Kwévoël.</i>	157
<i>Figure 9-1: Mass Flow Scheme using Secondary Materials in Cement Manufacture</i>	189
<i>Figure 9-2: Relationship between secondary materials input and possible downstream receptors</i>	192
<i>Figure 9-3: Maximum daily TSP</i>	197
<i>Figure 9-4: Highest daily predicted PM10 concentrations</i>	198
<i>Figure 9-5: Highest daily predicted NO<sub>x</sub> concentrations</i>	199
<i>Figure 9-6: Highest daily predicted SO<sub>2</sub> concentrations</i>	200
<i>Figure 9-7: Highest daily predicted CO concentrations</i>	201
<i>Figure 9-8: Highest daily predicted Metals concentrations</i>	202
<i>Figure 9-9: Highest daily predicted Dioxin concentrations</i>	203
<i>Figure 9-10: Highest daily predicted HCl concentrations</i>	204
<i>Figure 9-11: Highest daily predicted HF concentrations</i>	205
<i>Figure 9-12: Highest daily predicted Hg concentrations</i>	206
<i>Figure 9-13: Highest daily predicted TOC concentrations</i>	207
<i>Figure 9-14: Highest daily predicted Cd and Ti concentrations</i>	208
<i>Figure 9-15: Roles in the Waste hierarchy</i>	214
<i>Figure 9-16: Waste Management Costs for Plastics</i>	215
<i>Figure 9-17: Waste Management Costs for Tyres</i>	215
<i>Figure 9-18: Xylene Trial burn: SK8 VOC Measurements by external monitoring group (Levego)</i>	224

## GLOSSARY OF TERMS

Aggregates	Crushed stone, sand and gravel. Concrete and mortar are made by using aggregates mixed with cement and water.
Absorbent	Solid material that removes components from a gas or liquid.
Alkaline conditions	Condition of high pH where acidic compounds could be neutralized or acid-base reactions can take place.
Bag filter	Dust collection device using fabric filter bags for cleaning exhaust gas from a process plant.
Baseline emission level	The historical or normal emission level of an entity in a process without changes to input material or changes to the process.
Best practice	Internationally recognized, most efficient / effective techniques applied in manufacturing and production processes.
Biomass	A material of biological nature that is continuously generated by industrial processes or human activity.
Blending silo	Stores and blends finely ground materials
Bypass system	Arrangement whereby material or gas flow is directed around the normal process equipment, and not through it.
By-products	By-products are materials which are co-produced in manufacturing processes. Fly ash from coal combustion in electricity generation, and blast furnace slag from the production of iron are two examples.
Calciner	See "Pre-calciner"
Carbonaceous Spent Pot Lining (CSPL)	The carbonaceous portion of the SPL is the carbon lining that forms the cathode material that is used in the aluminium smelting process.
Carcinogens	Cancer causing substance or agent.
Cement (Portland Cement)	Hydraulic cement (that not only hardens by reacting with water but also forms a water-resistant product) produced by grinding clinker, (essentially calcium silicates), together with about 5% gypsum (calcium Sulphate, which is added to regulate the cement setting time). The name "Portland cement" is derived from the similarity in colour of cement after setting to the grey slate from Portland, UK.
Clinker	Nodular to powdery material produced in a rotary kiln by heating a blended, finely ground mixture of limestone (or calcium carbonate), shale (or other suitable material for silica and alumina), and a source of iron oxide to a temperature of approximately 1450°C
Coal mill	The plant required to dry and grind coal to produce a fuel for kiln firing.
Combustion	Reaction of a fuel with oxygen
Combustion efficiency	Indication of completeness of combustion of organic material (containing carbon) to carbon dioxide (CO <sub>2</sub> )
Condensation	Phase change of vapour to liquid
Cooler	Cools the clinker discharged from a cement kiln (at about 1100°C) to typically less than 200°C prior to transport to storage.
Cooler – Grate type	Cooling is achieved by cross-flow air blown through a clinker layer travelling slowly on a reciprocating grate which consists of perforated plates.

Cooler – satellite type	Nine to eleven tubes arranged peripherally at the discharge end of the rotary kiln. Hot clinker enters the tubes through inlet ports and passes through the tubes in counter current flow to cooling air. Also called a planetary cooler.
Co-processing	Utilization of alternative fuel and raw materials for the purpose of energy and resource recovery. Co-processing in cement manufacturing means substituting scarce primary energy and virgin raw materials with waste materials.
Counter current	Solid material and gas flowing in opposite directions. In all kiln systems the solid material moves counter current to the hot combustion gases.
“De novo” effect	The reformation of dioxins and furans is known to occur by “de novo” synthesis within the window of cooling from 450 to 200° C.
Effluent	A liquid waste stream.
Excess air	Ensures complete combustion of fuel due to the presence of excess oxygen (O <sub>2</sub> )
Extender (Pozzolanic)	See Pozzolan.
Extender (Filler)	See Non-Deleterious Materials
Flue gas	Exhaust gas from a combustion process.
Fly ash	A by-product from coal-fired power stations. Fly ash can be added to Portland cement as an extender or NDM (Non-Deleterious Materials)
Fossil fuel	A general term for combustible deposits of carbon in reduced (organic) form and of biological origin, including coal, oil, natural gas, and oil shale.
Greenhouse gases	Gases in the earth’s lower atmosphere that may contribute to global warming, of which CO <sub>2</sub> is a major component
Grate clinker cooler	Consists of a perforated grate through which cold air is blown, enclosed in a rectangular chamber. A bed of clinker up to 0.5 m deep moves along the grate.
Hazardous Waste	A material defined by regulation or legislation as flammable, explosive, corrosive or toxic, therefore requiring special handling or disposal
Heavy metals	All metals heavier than Titanium (4.51 g/cm <sup>3</sup> ) are termed heavy metals. The heavy metals make up a small proportion of the materials in the earth’s crust. Not all heavy metals are toxic and not all toxic heavy metals have the same toxicity.
Hydrocarbons	Chemical compounds consisting of the elements carbon and hydrogen used as building blocks in their structure
Incinerator	Plant used for the combustion of waste materials to yield a non-combustible residue or ash and exhaust gases, such as carbon dioxide and water.
Kiln dust	Particulate, solid material entrained in the exhaust gas from a cement kiln.
Kiln feed	Homogenised raw meal added to a rotary cement kiln at a controlled rate.
Leachate	Contaminated water or a solution with the potential to cause pollution, if the liquid is permitted to percolate through soil to ground water.
Lepol kiln	A kiln in which the feed is preheated on a horizontal travelling grate before entering the kiln.

Life cycle	Industrial processes involved in production including upstream extraction, manufacturing, distribution, use, and re-use or disposal of resulting waste materials
Limestone	Rock consisting essentially of carbonates with the most important constituents being calcite (CaCO <sub>3</sub> ).
Mineral additions	In blended (or “composite”) cements, a portion of the cement consists of materials (mineral additions) originating from natural or industrial sources such as blast furnace slag
Non-Deleterious Materials	Materials that can be added at the clinker grinding stage that do not have any negative effects on the cement performance. There are limits to the quantities of extenders that can be added to the cements based on the relevant SANS specification (SANS 50197).
Organic material	Chemical compound from natural sources with carbon as its core element
Oxidizing conditions	High oxygen content allowing complete oxidation of compounds (see excess air)
Physico-chemical absorption	Absorption due to chemical reaction and physical inclusion
Planetary Clinker Cooler	Refer to Cooler – satellite type
Pozzolan	A material that, although itself not cementitious, contains silica (and alumina) in a reactive form and is able to combine with lime in the presence of water to form compounds with cementitious properties.
Pre-calciner	A fluidized reaction vessel located above the feed end of the kiln which enables preheated kiln feed to be calcined before entering the kiln.
Preheater	Before entering the kiln, the kiln feed is preheated by suspension in the hot kiln exhaust gas stream in several cyclone stages (from 1 to 6) arranged vertically. The cyclone tower is known as the preheater.
Quarrying	Extracting raw materials from the earth.
Raw meal	Raw materials that are dried and ground in defined and well-controlled proportions in a raw mill
Raw mill	The plant for proportioning, drying and grinding the raw materials used for cement production.
Reducing conditions	Low oxygen content not allowing complete oxidation of compounds by oxygen
Refractory Spent pot lining (RSPL)	Waste refractory bricks which have been used for thermal protection of the pots at an aluminium smelter
Residues	Unwanted materials left by a manufacturing process.
Retention time	Time taken for material to pass through a process at the optimal operating conditions.
Rotary kiln	An inclined rotating steel cylinder lined with refractory bricks used to produce cement clinker.
Rotary kiln burner	Positioned at the kiln discharge end (firing end) to introduce fuel to the kiln process.
Scrubber	Equipment to remove impurities from a gas stream using a wet or dry process.
Secondary materials	Waste or by-products used in cement manufacturing as alternatives to fossil fuels and natural raw materials.
Shale	An argillaceous sedimentary rock

Sintering	Formation of clinker minerals in the cement kiln.
Stack	A chimney that exhausts gas from various stages in the cement manufacturing process.
Sustainable development	The ability of the present generation to continually meet its needs without compromising the ability of future generations to meet theirs.
Trace elements	Chemical elements present in minute quantities.
Turbulence	Condition under which intense and aggressive mixing and contact of materials occurs.
Volatility	Tendency of a chemical compound to form vapour under a given set of conditions.
Waste	An undesirable or superfluous by-product, emission, or residue of a process or activity which has been discarded, accumulated or stored for the purpose of further use by another process.

## ABBREVIATIONS

ACMP	Association of Cementitious Material Producers
AFR	Alternative fuels and raw materials
ANSI	American National Standards Institute
APPA	Atmospheric Pollution Prevention Act (No 45 of 1965)
BAT	Best Available Techniques
BCHS	Baseline Community Health Survey
BID	Background Information Document
BEP	Best Environmental Practice
CAPCO	Chief Air Pollution Control Officer
CHRA	Community Health Risk Assessment
DEAT	Department of Environmental Affairs and Tourism
DRE	Destruction and Removal Efficiency
DWAF	Department of Water Affairs and Forestry
EA	Environmental Assessment
EAP	Environmental Assessment Practitioner
EC	European Community
ECA	Environmental Conservation Act (Act 73 of 1989)
EIA	Environmental Impact Assessment
EMP	Environmental Management Plan
EPA	Environmental Protection Agency
ESP	Electrostatic Precipitator
ETR	Environmental technical Review
EU	European Union
FCC	Fluidized catalyst cracking
g	Gram
LEDET	Limpopo Department of Economic Development, Environment and Tourism
HAZOP	Hazard and operability study
HCS	Hazardous Chemical Substances
HM	Heavy metals
I&APs	Interested and Affected Parties
IDP	Integrated Development Plan
ISO	International Standards Organization
kg	Kilogram
kJ	Kilojoule
kPa	Kilopascal
LCA	Life Cycle Assessment
LOI	Loss on ignition

m <sup>3</sup>	Cubic meter
MES	Marsh Environmental Services
MHSA	Mine Health and Safety Act (No 29 of 1996)
MJ	Megajoule
MSDS	Material safety and data sheet
NDM	Non-Deleterious Materials
NEMA	National Environmental Management Act (Act 107 of 1998)
ng	Nanogram (1 x 10 <sup>-9</sup> grams)
Nm <sup>3</sup>	Normal or standard volume under standard conditions (0°C & 1.01 bar)
OEL	Occupational exposure limits
OH&S	Occupational Health and Safety
OSHAct	Occupational health and safety act (No 85 of 1993)
OSHAS	Occupational health and safety management systems (British)
pH	Acidity scale 1 to 14
PM10	Particulate matter smaller than 10 µm
POPs	Persistent organic pollutants
PoSS	Plan of Study for Scoping
ppb	Parts per billion
PPC	Pretoria Portland Cement
PPE	Personal protective equipment
PPM	Public Participation Meeting
ppm	Parts per million
PPP	Public Participation Process
RDF	Refuse derived fuels
SANS	South African National Standard
SHE	Safety, Health & Environment
SHEQ	Safety, Health, Environment & Quality
SK1	PPC equipment terminology (Plant & Kiln number, S=Slurry; PE=Port Elizabeth; DB=Dwaalboom; H=Hercules; D=De Hoek, K=Kiln)
SM	Secondary materials
SP	Suspension (or cyclone) preheater kiln
PC	Calcliner kiln (which also has a cyclone preheater)
SPL	Spent Pot Lining
SR	Scoping Report
T	Temperature
TEQ	Toxicity Equivalent
TCLP	Toxicity Characteristic Leaching Procedure
TOC	Total organic carbon
UNEP	United Nations Environment Programme

VOC	Volatile organic compound
WBCSD	World Business Council for Sustainable Development
WDF	Waste derived fuel
WUL	Water use Licence
µg	Microgram

S=Slurry; PE=Port Elizabeth; DB=Dwaalboom; H=Hercules; D=De Hoek.

## CHEMICAL ABBREVIATIONS

Ag	Silver
Al <sub>2</sub> O <sub>3</sub>	Aluminium oxide
As	Arsenic
Ba	Barium
Be	Beryllium
BTX	Benzene, toluene, xylene
C <sub>6</sub> H <sub>6</sub>	Benzene
CaCO <sub>3</sub>	Calcium carbonate
CaO	Calcium oxide
CaSO <sub>4</sub>	Calcium sulphate
CaSO <sub>4</sub> .2H <sub>2</sub> O	Gypsum
Cd	Cadmium
CFCs	Chlorofluorocarbons
CH <sub>4</sub>	Methane
CO	Carbon monoxide
Co	Cobalt
CO <sub>2</sub>	Carbon dioxide
Cr	Chromium
Cu	Copper
F	Fluoride
Fe <sub>2</sub> O <sub>3</sub>	Iron oxide
FeS <sub>2</sub>	Iron sulphide
H <sub>2</sub> O	Water
HCB	Hexachlorobenzene
HCl	Hydrogen chloride (hydrochloric acid)
HF	Hydrogen fluoride (hydrofluoric acid)
Hg	Mercury
K <sub>2</sub> O	Potassium oxide
MgO	Magnesium oxide
Mn	Manganese
Mn <sub>2</sub> O <sub>3</sub>	Manganese trioxide
NH <sub>3</sub>	Ammonia
N <sub>2</sub>	Nitrogen
Na <sub>2</sub> O	Sodium oxide
Na <sub>2</sub> SO <sub>4</sub>	Sodium sulphate
Ni	Nickel
NO <sub>x</sub>	Nitrogen oxides

O <sub>2</sub>	Oxygen
P <sub>2</sub> O <sub>5</sub>	Phosphorus pentoxide
PAH	Polyaromatic hydrocarbons
Pb	Lead
PCBs	Polychlorinated biphenyls
PCDDs	Polychlorinated dibenzodioxins
PCDFs	Polychlorinated dibenzofurans
Pd	Palladium
Pt	Platinum
Rh	Rhodium
Sb	Antimony
Se	Selenium
SiO <sub>2</sub>	Silicon dioxide
Sn	Tin
SO <sub>2</sub>	Sulphur dioxide
SO <sub>3</sub>	Sulphur trioxide
SOx	Sulphur oxides
TCE	Trichloroethylene
TCM	Tetra-chloromethane
Te	Tellurium
Ti	Titanium
TiO <sub>2</sub>	Titanium dioxide
Tl	Thallium
V	Vanadium
Zn	Zinc
°C	Degrees Celcius